



WARRIOR WINCH MODIFICATION FOR ARB BUMPER MOUNT

**This modification applies to Winches:
C9500EWX12SYN and C1200EWX12**

Page: 1 OF 3



Tools Needed: 6mm Allen Wrench & 3mm Allen Wrench

Procedure:

1. Using the 6mm Allen Wrench, remove the two screws that attach the drum support to the tie bars. (See Figure #1)



(Figure #1)

2. Pull the gearbox and drum support away from the drum. (See Figure #2)



(Figure #2)

Atlantic British Ltd.[®]

3. Flip the adjoined piece over to reveal 10 screws. (See Figure #3)



(Figure #3)



(Figure #4)

4. Undo the 10 screws using a 3mm Allen Wrench. Be sure to hold the gearbox to the drum support when removing the screws. (See Figure #4)
5. Next, rotate the gearbox against the drum support, finding your desired position. (See Figure #5)



(Figure #5)

6. Make sure that your new placement allows room for the gearbox switch on your bumper. (See Figure #6)



(Figure #6)

Atlantic British Ltd.[®]

7. Once the gearbox is in proper position, insert and tighten the ten screws holding the gearbox to the drum support.
8. Fit the tie bars back through the gearbox and drum support unit. (See Figure #7)



(Figure #7)

9. Tighten the two screws to the tie bars. (See Figure #8)



(Figure #8)



(Figure #9)

10. Your gearbox switch should no longer interfere with your ARB Bar! (See Figure #9)

To remove the control box

1. Unscrew the control box from the body.
2. Mount to preferred area using extended 5-foot cables.

Atlantic British Ltd.[®]

www.AtlanticBritish.com • 800-533-2208 • Fax 518-664-6641 • Phone 518-664-6169